

Gas 220⁺ Ace - 160

TECHNICAL
SPECIFICATION
SHEET

September 2017

This is a quick reference specification sheet, full details can be found in the Gas 220 Ace installation/service manual via remeha.co.uk

OVERVIEW

MODEL : Gas 220 Ace - 160	CE PIN 0063CQ3781
Rated Output kW (80/60°C)	152.1
Rated Output kW (50/30°C)	161.1
Weight (dry incl Packaging) kg	235
Overall Dim WxHxD mm	800x1662x657
No of sections : One piece casting	Cast Aluminum Monoblock
SBEM Seasonal Efficiency %: GCV ⁽¹⁾	95.9
Efficiency - Full Load 100%: NCV ⁽⁴⁾	97.5
Efficiency - Part Load 30%: NCV ⁽⁵⁾	108.5
Stand-by Heat Loss kW :	0.191

BURNER TYPE PRE MIX

Std Fuel Available	Natural Gas
Fuel Consumption M ³ /h	16.5 NG max
Fuel Consumption M ³ /h	6.3 LPG max
Flame Protection	Ionisation
Ignition	Electronic
Noise level dB(A) at 1 metre	58.7
Optional Fuel	Propane
LGP adjustment (*)	
Gas Connection size BSP	1" (M)
Min/Max Gas pressure mbar	17-25 NG
Min/Max Gas pressure mbar	37-50 LPG
NOx (dry, 0% O ₂) EN483 EN 15420	36 Mg/kWh

FLUE/AIR INLET

Flue diameter mm I/D	150
Air inlet diameter mm I/D	150
Mass flue gas flow rate kg/hr	57 - 277
Flue gas temperature °C	32-66
Maximum counter pressure PA	200

CONTROLS/OPTIONS

<p>STANDARD -</p> <ul style="list-style-type: none"> On/Off, 0-10v dc, Open Therm High limit protection and low water protection Volt free common alarm and boiler run indication Manual override Safety Interlocks Hours run indication 	<p>OPTIONAL - Optimising compensators for single and multiple boilers</p> <ul style="list-style-type: none"> Cascade kits - multiple boiler pipework kits Low loss headers Outside sensor for simple weather compensation
--	--

ERP DATA ENERGY LABEL

Seasonal Space Efficiency % ⁽²⁾	NA
Energy Efficiency Class ⁽²⁾	NA
Sound Power Levels Lwa Indoors dB	67
Useful Efficiency - Full Load (GCV)% ⁽³⁾	87.8
Useful Efficiency - Part Load (GCV)% ⁽³⁾	97.8
NOx (Dry, 0% O ₂) Mg/kWh ⁺	35

HYDRAULICS

Water contents ltrs	17
Resistance @ 20°C mbar	190
Nom Flow Rate @ 20° C l/s	1.81
Condensate Connection	40mm OD
Connection Size " BSP	1 ^{1/4} "(M)
Std Operating Temp °C	20-90
Max Operating Temp °C	90
High Limit Set Point °C	110
Max operating pressure bar	5
Min operating pressure bar	0.8

ELECTRICAL

Power Supply	230v - 1ph - 50hz
Power Consumption W	5.3 - 275
Modulating input V dc	0-10
Fuse Rating amps	6.3
Insulation Class IP	IPX1B

(1) In accordance with the Non Domestic Building Services Compliance Guide 2013 Edition-For use in England

(2) In accordance with EU 811 & 812 / 2013 Energy Labeling Regulations

(3) In accordance with EU 813 & 814 / 2013 Eco Design Regulations

(4) @ 80/60 °C Nett (EN 92/42)

(5) @ 50/30 °C nett (92/42)

(*) See installation and service manual