

GAS 310ECO PRO 500

TECHNICAL SPECIFICATION SHEET

October 2017

This is a quick reference specification sheet, full details can be found in the Gas 310 Eco Pro installation and service guide via remeha.co.uk

OVERVIEW

MODEL : Gas 310 Eco Pro 500	8 sections
Rated Output kW (80/60°C)	92 - 461
Rated Output kW (50/30°C)	497
Weight (dry) kgs	495
Overall Dim WxDxH mm	716 x 2172 x 1500
SBEM Seasonal Efficiency % GC ⁽¹⁾	96.09
Efficiency-Full Load 100% NCV: (2)	98.3
Efficiency-Part Load 30% NCV: (3)	108.6
stand-by Heat Loss % : (*)	0.13

BURNER TYPE PRE MX

Std Fuel Available	Natural Gas
Fuel Consumption M ³ /h	49.6 (max)
Flame protection	Ionisation
Ignition	Electronic
Gas connection size BSP	2" (F)
Acoustic level dB (A) at 1 metre (**)	56
NO _x (Dry, 0% O ₂) Mg/KWh	29
Min/Max Gas pressure mbar	17 - 100

CONCENTRIC FLUE/AIR INLET

Flue diameter mm I/D	250
Air inlet diameter mm I/D	250
Residual fan duty Pa	150
Mass flue gas flow rate kg/hr	160 - 789
Flue gas temperature @ 80/60°C	30 - 80

CONTROLS/OPTIONS

STANDARD - On/Off 0-10v dc, Open Therm High limit protection Low water protection Volt free common alarm Manual override Modulating (20 - 100%, avg.) Safety interlocks Hours run indication Boiler run indication	OPTIONS - Optimising/Compensators for multiple and single boilers Gas leak detection option fitted to gas valve Water Press Switch - for system pressure Second return 65mm Flanged 80mm PN16 Air Inlet Filter connects to boiler air supply
--	--

HYDRAULICS

Water Content ltrs	82
Resistance @ 11°C mbar	364
Resistance @ 20°C mbar	110
Nom Flow Rate @ 11°C l/s	10.03
Nom Flow Rate @ 20°C l/s	5.51
Min flow Rate m ³ /h	5.9
Condensate Outlet (mm) I/D	32
Connection size flanged (#)	NW 80
Std operating temp °C	20 - 90
Max operating temp °C	90
High limit set point °C	110
Max operating pressure bar	7
Min operating pressure bar	0.8

ELECTRICAL

Power supply	230v - 1ph - 50hz
Power consumption W	6 - 543
Modulating input V dc	0 - 10
Start current amps	4
Fuse rating amps	10
Controls voltage	24 (max)
Insulation class IP	X1B
Run current amps	1.4

(1) In accordance with the Non Domestic Building Services Compliance Guide 2013 Edition-For use in England

(2) @ 80/60 oC Nett (EN 92/42)

(3) @ 30 oC Nett (EN 92/42)

(*) (EN15420) @ 30 °C T = Boiler temperature - ambient temperature (without heat exchanger insulation kit)

(**) Maximum for room sealed operation

(#) Flow 80mm return 65mm both flanged NW 80 DIN 2576 - (PN16)