

GAS 610ECO PRO 1300

TECHNICAL SPECIFICATION SHEET

October 2017

This is a quick reference specification sheet, full details can be found in the Gas 610 Eco Pro installation and service guide via remeha.co.uk

OVERVIEW

MODEL : Gas 610 Eco Pro 1300	2 x 10 sections
Rated Output kW (80/60°C)	158 - 1202
Rated Output kW (50/30°C)	1303
Weight (dry) kgs	1095
Overall Dim WxDxH mm	1460 x 1862 x 1726
SBEM Seasonal Efficiency % GC ₄₁	95.75
Efficiency-Full Load 100% NCV: (2)	98.5
Efficiency-Part Load 30% NCV: (3)	108.1
stand-by Heat Loss % : (*)	0.11

BURNER TYPE PRE MX

Std Fuel Available	Natural Gas
Fuel Consumption M ³ /h	129.2 (max)
Flame protection	Ionisation
Ignition	Electronic
Gas connection size BSP	2 x 2" (F)
Acoustic level dB (A) at 1 metre (**)	58
NOx (Dry, 0% O ₂) Mg/KWh	26
Min/Max Gas pressure mbar	17 - 30 NG

CONCENTRIC FLUE/AIR INLET

Flue diameter mm I/D	350
Air inlet diameter mm I/D	250 x 2
Residual fan duty Pa	150
Mass flue gas flow rate kg/hr	410 - 2052
Flue gas temperature @ 80/60°C	30 - 80

CONTROLS/OPTIONS

STANDARD - On/Off 0-10v dc, Open Therm High limit protection Volt free common alarm Manual override Modulating (10-100%) Safety interlocks Hours run indication Boiler run indication	OPTIONAL - Optimising/Compensators for multiple and single boilers Gas leak detection option fitted to gas valve Second return 65mm Flanged 80mm PN16 Water Pressure Switch for system pressure Air Inlet Filter connects to boiler air supply Two into one inlet manifold option
--	--

HYDRAULICS

Water Content ltrs	104 (per module)
Resistance @ 11°C mbar	435 (per module)
Resistance @ 20°C mbar	130 (per module)
Nom Flow Rate @ 11°C l/s	13.07 (per module)
Nom Flow Rate @ 20°C l/s	7.19 (per module)
Min flow Rate m ³ /h	7.8 (per module)
Condensate Outlet mm I/D	32 x 2
Connection size flanged (#)	NW 80
Std operating temp °C	20 - 90
Max operating temp °C	90
High limit set point °C	110
Max operating pressure bar	7
Min operating pressure bar	0.8

ELECTRICAL

Power supply	2 x 230v - 1ph - 50hz
Power consumption W	14 - 1446
Modulating input V dc	0 - 10
Start current amps	2 x 4
Fuse rating amps	2 x 10
Controls voltage	2 x 24 (max)
Insulation class IP	X1B
Run current amps	2 x 3.8

(1) In accordance with the Non Domestic Building Services Compliance Guide 2013 Edition-For use in England

(2) @ 80/60 oC Nett (EN 92/42)

(3) @ 30 oC Nett (EN 92/42)

(*) (EN15420) @ 30 °C T = Boiler temperature - ambient temperature (without heat exchanger insulation kit)

(**) Maximum for room sealed operation

(#) Flow 80mm return 65mm both flanged NW 80 DIN 2576 - (PN16)