

<p>Quick reference specification sheet, full details can be found in the P420 series installation/service guide. General details: Corrosion resistant cast iron sectional boiler, jointed by conical nipples and ceramic rope, designed with three passes for high efficiency and low NOx emission. Large insulated door (hinged left or right) allowing easy access for cleaning. Powder coated enamel steel casing c/w fibreglass insulation. All of the P420 boiler range are supplied un-assembled for delivery to site. CE approved. Boiler efficiency data to 92/42-EEC. +</p>	<h1 style="margin: 0;">P420+</h1> <h2 style="margin: 0;">12</h2> <p style="margin: 0;">TECHNICAL SPECIFICATION SHEET</p> <p style="margin: 0;">June 2016</p>
---	--

OVERVIEW	
MODEL : P420	
Rated Output kW	670
Weight (dry) kgs	As per technical manual
Overall Dim WxHxD mm	1000 x 1690 x 2465
Radiated Losses W *	494
Efficiency % : NCV Full load (3)	88
Seasonal Efficiency : % GCV	82.2 (Avg)

BURNER TYPE - PRESSURE JET	
Fuel Available	Nat Gas
Fuel Consumption : max	Check Burner details
Noise levels dB (A)	Check Burner details
Min op Gas Press bar	Check Burner details

FLUE/AIR INLET	
Diameter mm	300
Flue type	Conventional
Chamber Resist. mbar	2.5
Flue Gas Flow kgs/hr Gas : (1)	1207
Flue Gas Flow kgs/hr Oil : (1)	1116
Flue Gas Temperature °C : (2)	< 220

CONTROLS/OPTIONS	
<p>STANDARD -</p> <ul style="list-style-type: none"> On / Off Thermostat High limit Thermostat High / Low indication Temperature indication Volt free run/lock indication 3 Positions switch auto/man/test L/O lamp On/Off switch 10amp CB 	<p>OPTIONAL -</p> <ul style="list-style-type: none"> Hours run meters Modulating (via burner)

HYDRAULICS	
Water Content ltrs	538
Resistance @ 11°C mbar	109.2
Resistance @ 20°C mbar	33
Nom Flow Rate @ 11°C l/s	14.55
Nom Flow Rate @ 20°C l/s	8.0
Min flow Rate l/s : #	3.54
Max Op Press bars	6
Test Press bars	As per Assembly Manual
Min Return temps °C	50
Connection size	3"
Std Operating Temp	80
Max Operating Temp	90
High limit Set Point °C	110

ELECTRICAL	
Volatge	230.1.50
Fuse rating amps	10Amp
<p>Note: 1ph burners obtain their power supply via the boiler. 3ph burners require a 3ph supply + a 1ph to the boiler</p>	

(1) Boiler at full output average temperature 80/30 C (70 °C mean)
 (2) With boiler temperature: 80 °C and ambient temperature: 20 °C
 (3) 70 °C mean temperature
 * Maintenance consumption refer to boiler installation/service manual
 # Based delta t of 45 °C between the boiler and the room temperature
 ## @ 12 bar pump pressure