

Quick reference specification sheet, full details can be found in the P420 series installation/service guide. General details: Corrosion resistant cast iron sectional boiler, jointed by conical nipples and ceramic rope, designed with three passes for high efficiency and low NOx emission. Large insulated door (hinged left or right) allowing easy access for cleaning. Powder coated enamel steel casing c/w fibreglass insulation. All of the P420 boiler range are supplied un-assembled for delivery to site. CE approved. Boiler efficiency data to 92/42-EEC. +

P420+

13

TECHNICAL
SPECIFICATION
SHEET

June 2016

OVERVIEW

MODEL : P420	
Rated Output kW	720
Weight (dry) kgs	As per technical manual
Overall Dim WxHxD mm	1000 x 1690 x 2625
Radiated Losses W *	505
Efficiency % : NCV Full load (3)	88
Seasonal Efficiency : % GCV	82.2 (Avg)

BURNER TYPE - PRESSURE JET

Fuel Available	Nat Gas
Fuel Consumption : max	Check Burner details
Noise levels dB (A)	Check Burner details
Min op Gas Press bar	Check Burner details

FLUE/AIR INLET

Diameter mm	300
Flue type	Conventional
Chamber Resist. mbar	2.5
Flue Gas Flow kgs/hr Gas : (1)	1297
Flue Gas Flow kgs/hr Oil : (1)	1200
Flue Gas Temperature °C : (2)	< 220

CONTROLS/OPTIONS

STANDARD - On / Off Thermostat High limit Thermostat High / Low indication Temperature indication Volt free run/lock indication 3 Positions switch auto/man/test L/O lamp On/Off switch 10amp CB	OPTIONAL - Hours run meters Modulating (via burner)
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------

HYDRAULICS

Water Content ltrs	581
Resistance @ 11°C mbar	132.17
Resistance @ 20°C mbar	40
Nom Flow Rate @ 11°C l/s	15.64
Nom Flow Rate @ 20°C l/s	8.60
Min flow Rate l/s : #	3.8
Max Op Press bars	6
Test Press bars	As per Assembly Manual
Min Return temps °C	50
Connection size	3"
Std Operating Temp	80
Max Operating Temp	90
High limit Set Point °C	110

ELECTRICAL

Volatge	230.1.50
Fuse rating amps	10Amp
	Note: 1ph burners obtain their power supply via the boiler. 3ph burners require a 3ph supply + a 1ph to the boiler

- (1) Boiler at full output average temperature 80/30 C (70 °C mean)
 (2) With boiler temperature: 80 °C and ambient temperature: 20 °C
 (3) 70 °C mean temperature
 * Maintenance consumption refer to boiler installation/service manual
 # Based delta t of 45 °C between the boiler and the room temperature
 ## @ 12 bar pump pressure