

# QUINTA<sup>+</sup> PRO 30

TECHNICAL  
SPECIFICATION  
SHEET

August 2017

This is a quick reference specification sheet, full details can be found in the Quinta Pro installation/service guide via [remeha.co.uk/documents](http://remeha.co.uk/documents).

## OVERVIEW

MODEL : Quinta Pro 30	GC No : 41-288-15
Rated Output kW (80/60°C)	29.8
Rated Output kW (50/30°C)	31.4
Weight (dry) kgs	53
Overall Dim WxHxD mm	500x750x500
No of sections:	One piece casting
SBEM Seasonal Efficiency %: GCV <sup>(1)</sup>	97.60
Efficiency - Full Load 100%: NCV <sup>(4)</sup>	99.4
Efficiency - Part Load 30%: NCV <sup>(5)</sup>	110.4
Stand-by Heat Loss kW :	0.101

## BURNER TYPE PRE MIX

Std Fuel Available	Natural Gas
Fuel Consumption M <sup>3</sup> /h	3.2 NG max
Fuel Consumption M <sup>3</sup> /h	1.2 LPG max
Flame Protection	Ionisation
Ignition	Electronic
Noise level dB(A) at 1 metre	38
Optional Fuel	Propane
LGP adjustment (*)	
Gas Connection size BSP	3/4" (M)
Min/Max Gas pressure mbar	17-25 NG
Min/Max Gas pressure mbar	37-50 LPG
NOx (dry, 0% O <sub>2</sub> ) EN483 EN 15420	37 Mg/kWh

## CONCENTRIC FLUE/AIR INLET

Flue diameter mm I/D	80
Air inlet diameter mm I/D	125
Mass flue gas flow rate kg/hr	14-50
Flue gas temperature °C	30-65
Maximum counter pressure PA	70

## CONTROLS/OPTIONS

<p>STANDARD -</p> <ul style="list-style-type: none"> <li>On/Off, 0-10v dc, Open Therm</li> <li>High limit protection and low water protection</li> <li>Volt free common alarm and boiler run indication</li> <li>Manual o/ride</li> <li>Hot water priority facility (3 way valve or pump)</li> <li>Two Safety Interlocks</li> <li>Hours run indication</li> <li>Flue - concentric connection (***) (#)</li> </ul>	<p>OPTIONAL - Optimising compensators for single and multiple boilers</p> <ul style="list-style-type: none"> <li>Cascade kits - multiple boiler pipework kits</li> <li>Low loss headers</li> <li>Outside sensor fir simple weather compensation</li> <li>Hot water priority kits - pump or valve kits</li> <li>Relay kits for single and multiple controls - 230v switching relay</li> </ul>
---	--

## ERP DATA ENERGY LABEL

Seasonal Space Efficiency % <sup>(2)</sup>	94
Energy Efficiency Class <sup>(2)</sup>	A
Sound Power Levels Lwa Indoors dB	46
Annual Energy Consumption Gj	91
Useful Efficiency - Full Load (GCV)% <sup>(3)</sup>	89.5
Useful Efficiency - Part Load (GCV)% <sup>(3)</sup>	99.5
NOx (Dry, 0% O <sub>2</sub> ) Mg/kWh <sup>+</sup>	32

## HYDRAULICS

Water contents ltrs	4.3
Resistance @ 11°C mbar	231
Resistance @ 20°C mbar	70
Nom Flow Rate @ 11° C l/s	0.65
Nom Flow Rate @ 20° C l/s	0.36
Min Flow Rate m <sup>3</sup> /hr	0.4
Condensate Connection	3/4" OD
Connection Size " BSP	1 1/4"(M)
Std Operating Temp °C	20-90(**)
Max Operating Temp °C	90 (**)
High Limit Set Point °C	110 (**)
Max operating pressure bar	4
Min operating pressure bar	0.8
Min operating pressure bar	0.3 o/v

## ELECTRICAL

Power Supply	230v - 1 ph - 50hz
Start Current amps	1.8
Power Consumption W	18 - 39
Modulating input V dc	0-10
Fuse Rating amps	6.3
Controls Voltage	23 (max 4va)
Insulation Class IP	X4D

(1) In accordance with the Non Domestic Building Services Compliance Guide 2013 Edition-For use in England

(2) In accordance with EU 811 & 812 / 2013 Energy Labeling Regulations

(3) In accordance with EU 813 & 814 / 2013 Eco Design Regulations

(4) @ 80/60 °C Nett (EN 92/42)

(5) @ 50/30 °C nett (92/42)

(\*) See installation and service manual

(\*\*) Open vented option maximum operating temperature 75°C high limit 95°C

(\*\*\*) For conventional or room sealed operation

(#) Flue adaptor available for CLV systems