

# 1250<sup>+</sup> INDIRECT

## TECHNICAL SPECIFICATION SHEET

June 2016

This is a quick reference specification sheet, full details can be found in the 1250 Indirect installation/service guide via [remeha.co.uk/documents](http://remeha.co.uk/documents).

### MODEL: 1250 INDIRECT

Storage Volume (litres)	1250
Continuous perfo. at 45° (ltr/hr)	1870
1 <sup>st</sup> hour perfo. at 45° (ltr/hr)	3120
Water delivered at 40° (Itrs)	1206
Standing Loss / Day (kWh/24hr)	3.60

### CYLINDER MATERIAL: STAINLESS STEEL (DUPLEX 2205)

Primary Coil Rate at Maximum (kW)	97.9
Primary Coil Rate at Max (ltr/min)	60
Pressure drop across coil at max (bar)	0.25
Heat Up Time at Max (min)	40
Standing Loss per Year (kWh/24hr)	1314

### ERP DATA - DATA INFORMATION

Storage Volume (Itrs)	1250.0
The water heating energy class	C
standing Loss (W)	150.0

### MODEL DIMENSIONS

Diameter (mm)	1224
Height (mm)	1937
Weight empty (kg)	319
Weight full (kg)	1569

### CONNECTIONS - HYDRAULIC

Inlet (BSP)	1 1/2"
Outlet (BSP)	1 1/2"
Sensor pocket	1/2"
Primary flow & Return (BSP)	1 1/2"
Secondary Return (BSP)	1"

### CONNECTIONS - UNVENTED KIT

Pressure reducing valve	1 1/2" (6bar)
Pressure relieve valve	1" x 1 1/4"
Check valve (single)	1 1/2"
Expansion vessel size (Itrs)	150
Expansion vessel mounting	Floor
T & P Relieve valve size (BSP)	1 1/4"
T & P Relieve valve temperature	90 - 95°C
T & P Relieve valve pressure	10 bar
Tundish	1 1/4" x 1 1/2"
2 Port motorized heater	DN40 (1 1/2")

### CONNECTIONS - ELECTRICAL

Upper immersion heater	6 - 54kW (1 - 3ph)
Lower Immersion heater	N/A

### CONTROLS/OPTIONS

STANDARD -	OPTIONS -
<ul style="list-style-type: none"> <li>Installation Manual</li> <li>- Commissioning checklist</li> <li>- Service record</li> <li>Cold water control pack</li> <li>- Expansion vessel</li> <li>- Pressure reducing valve</li> <li>- Pressure relief valve</li> <li>- Tundish</li> <li>- Check valve</li> <li>- 2-port valve</li> </ul>	<ul style="list-style-type: none"> <li>Destratification loop kit</li> <li>Immersion heater 6-9kW (1ph)</li> <li>Immersion Heater 12-54kW (3ph)</li> <li>Temperature gauge</li> <li>Pressure gauge</li> </ul>

### NOTES -

1. Indirect cylinders tested in conformance with BS EN 12897:2006.
2. Indirect heat up times based on a 45oc temperature rise, based on a primary flow temperature of 80°C +/- 2°C