

Boiler type :	P320 – 5
Issue Date :	June 2012



TECHNICAL SPECIFICATION SHEET

Quick reference specification sheet full details can be found in the Quinta Pro Installation/Service guide.

General Details

Corrosion resistant cast iron sectional boiler, jointed by conical nipples and ceramic rope, designed with three passes for high efficiency and low NOx emission. Large insulated door (hinged left or right) allowing easy access for cleaning. Powder coated enamel steel casing c/w fibreglass insulation. All of the P320 Boiler Range can be supplied un-assembled or pre-assembled for delivery to site. CE approved. Boiler Efficiency data to 92/42-EEC

MODEL : P320		No of SECTIONS : 5	
Rated Output kW :	105 – 140	Efficiency % : NCV Full load ⁽³⁾	88
Weight (dry) kgs :	739	Seasonal Efficiency : % GCV	83.6
Overall Dim WxHxD mm :	796 x 1387 x 1151		
Radiated Losses % : *	0.14		
BURNER TYPE		Pressure Jet	
Fuel Available :	Nat Gas	Oil (35sec)	Dual Fuel
Fuel Consumption: max	Check burner details	13.48 Kg/hr ##	
Noise levels dB(A) :	Check burner details		
Min Op Gas Press mbar :	Check burner details		
HYDRAULICS			
Water Content ltrs :	116	Min Return Temp °C	50
Resistance @ 11°C Δt mbar :	20.26	Connection Size :	2½" Flanged
Resistance @ 20°C Δt mbar :	6.11	Std Operating Temp °C :	80
Nom Flow Rate @ 11° C Δt l/s	3.04	Max Operating Temp °C :	90
Nom Flow Rate @ 20° C Δt l/s :	1.67	High Limit Set Point °C :	110
Min Flow Rate l/s : #	0.74		
Max Op Press bars :	6		
Test Press bar :	As per Assembly Manual		
FLUE			
Diameter mm :	180	Flue Gas Flow kgs/hr Gas : ⁽¹⁾	250
Flue Type :	Conventional	Flue Gas Flow kgs/hr Oil : ⁽¹⁾	238
Chamber Resist. mbar :	+ 0.6	Flue Gas Temperature °C : ⁽²⁾	<210
ELECTRICAL			
Voltage :	230.1.50	Note: 1ph burners obtain their power supply via the boiler. 3ph burners require a 3ph supply + a 1ph to the boiler.	
Fuse rating amps :	10Amp		
CONTROL OPERATION			
Standard :	On / Off Thermostat	Temperature indication	L/O lamp
	High limit Thermostat	Volt free run/lock indication	On/Off switch
	High / Low	3 Position Switch Auto/Man/Test	10amp CB
Optional :	Hours Run Meters Modulating (via burner)		

(1) Boiler at full output average temperature 80/60°C (70°C mean)

(2) Boiler temperature: 80 °C, Ambient temperature: 20 °C

(3) 70°C average temperature

* Maintenance consumption refer to boiler installation/service manual

Based on Δt of 45°C

@ 12 bar pump pressure

Ours is a policy of continuous development, we therefore reserve the right to alter specifications without prior notification. Remeha Commercial accept no liability for any loss or damage rising from any errors or omissions that may be inadvertently contained in this specification sheet. ©